



Mixer Amplifier

Description:

The JMA-1030 /60 amplifiers are comprehensive, All-in-one mixer-Amplifier solutions for commercial and industrial applications. These low-cost units provide all necessary features in a simple building.

Features:

Three line and two microphone inputs with Euro block and RAC jack.
Acceptable wide range input level.
30Watts (JMA-1030) / 60Watts (JMA-1060) rated power output.
Advanced protection system includes current limiting
Over current and thermal protections.
Desktop and 19-inches rack mountable type two bands tone controls
Low distortion and low noise level Compact size and light weight
Ideal commercial and industrial use



Functions:

Controls
Front: 3 Channel Volume Control & Tone Control, Master Volume Rear: Line/MIC selector, Talk over level volume, Phantom Switch
Connectors
Euro Block for Channel 1-2 Input RCA Jack for Channel 3 Input Euro Block for Speaker Output
Message play: playback the recorded message with micro SD card on the rear panel
Media Player: MP3 play, Record to USB memory, Bluetooth.
Indicators: Power, Signal, -20dB, Clip and Protect
Protection: Current Limiting, Thermal & DC Offset Protection Cooling: Convection Cooling

Model	JMA-1030	JMA-1060
Rated Output Power	30W	60W
Input sensitivity / Impedance	MIC: -50dB/600ohm Line: 6dB/10kohm	
Power Supply Voltage	100-240V 50/60Hz	100-240V 50/60Hz
Power Consumption	40W	70W
Speaker Output	100V (333Ω), 70V (163Ω), 4Ω (11V)	100V (166Ω), 70V (82Ω), 4Ω (15V)
Free agency Response	80Hz-17 KHz (+1dB /-3dB)	
S/N Ratio	>80dB (with A-Weight)	
T.H.D	<1 at rated power, 1 kHz)	
Microphone input	-50dB/600Ω,unbalanced input	
Auxiliary input	0dBu/10KΩ, unbalanced input	
Tone Controls	Bass:100Hz(±10dB), Treble:10KHz(±10dB)	
Mute Function	MIC over other inputs	
Working Temperature	-10°C~+ 40° C	
Product Dimension (WxHxD)	280x60x200 mm	
Net Weight	4.2kg	5.0kg



Legende Integrated Industries
25 Mohamed El Nady St, 8th District, Nasr City

legende-ind.com
info@legenede.com