

Features:

Amplifiers

- User selectable constant voltage(100V/70V) and 4ohms outputs with power sharing mode

Controls

- Front: Power On/Off switch.

Rear: Volume Control, output selection (100V/70V/4ohm) switch for each channel. Ground lift switch.

Connectors

- Input: Euro block for Electronically Balanced Input for each channel.

- Output: Euro block for each channel.


- Dante : Custom option

Indicators: Sig, Clip, Protect & Power On.

Protections: Over Voltage, Under Voltage, over current with Fuse and over temperature Protection.

Cooling: Variable speed fan forced cooling.

Power sharing: Up to 480W output at one channel...





Model	JPA-4120DP	JPA-4240DP			
Rated Power (1kHz, THD 1%)	120W X 4	240W X 4			
Output Impedance	100V or 70V or 4 Ω				
Input sensitivity / Impedance	0dB / 20 kohm Balanced				
Frequency Response	50Hz - 15kHz				
T.H.D(1kHz,1/3 Rated Power)	0.1%				
Signal to Noise Ratio	90dB				
Power Source	AC 100~240 V, 50/60Hz				
Weight (Net)	7.3kg	7.5kg			
Dimensions (W x H x D)	483 x88 x 360	483 x88 x 360mm			

