

## Flood Light LED High Bay Light

**Code: LEG-HBL SERIE**

### Technical Data:

Product. UFO Led high bay light (ST-HBN)

Certification. SAA, TUV CE, RoHS

Warranty. 5 years

Lamp body. Die-cast aluminum

Light source. Nichia Led

Luminaire's Efficiency. 120~130Lm/W

Driver. Mean well / SINOCO

Finishing. Surface anti-ageing electrostatic  
spray processing

Super resistance to corrosion

Installation height. 4 - 12M

Application. Widely used in factory, ware  
house, parking lot and other large lighting  
area




### Technical parameter



Model	Power	Input voltage	Light Source	Luminous Flux	Luminaire's Efficiency	Product size	N.W	G.W	Packing (mm)
LEG-HBL-80W	80W	100-277VAC 50-60HZ	Nichia Led	10400Lm	130Lm/W	Ø285 * H185mm	2.78kg	3.6kg	L390 * W390 * H210mm
LEG-HBL-100W	100W	100-277VAC 50-60HZ	Nichia Led	13000Lm	130Lm/W	Ø285 * H185mm	2.78kg	3.6kg	L390 * W390 * H210mm
LEG-HBL-120W	120W	100-277VAC 50-60HZ	Nichia Led	15600Lm	130Lm/W	Ø340 * H187mm	4.97kg	5.8kg	L390 * W390 * H210mm
LEG-HBL-150W	150W	100-277VAC 50-60HZ	Nichia Led	19500Lm	130Lm/W	Ø340 * H187mm	4.97kg	5.8kg	L390 * W390 * H210mm
LEG-HBL-200W	200W	100-277VAC 50-60HZ	Nichia Led	26000Lm	130Lm/W	Ø400 * H196mm	5.12kg	6.8kg	L450 * W450 * H210mm
LEG-HBL-240W	240W	100-277VAC 50-60HZ	Nichia Led	31200Lm	130Lm/W	Ø400 * H196mm	6kg	7.4kg	L450 * W450 * H210mm




## Dimension









60W-100W



120W-240W



## PHOTOMETRIC CHARACTERISTIC




## MOUNTING STEP



Chain installation



Bitmap Steeve installation



U-shaped bracket installation

